



6 B 09 / 02548



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

REC'D 30 JUL 2004

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

AmBrewster

Dated 22 July 2004

Patents Form 1/77

Patents Act 1977
(Rule 1)



1/77
19 JUN 03 E816081-1/000558
P01/7700 0.00-0314183.5

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

DSM/jc/J1794

2. Patent application number

(The Patent Office will fill in this part)

0314183.5

18 JUN 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Westinghouse Brakes (UK) Limited
Foundry Lane
Chippenham
Wiltshire
SN15 1JB

Patents ADP number (if you know it)

8628448001

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

Seal Arrangement

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Jensen & Son,
70 Paul Street,
London,
EC2A 4NA.

JENSEN & SON
366-368 Old Street
LONDON
EC1V 9LT
ADP No. 00000968001

Patents ADP number (if you know it)

968001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description

4

Claim(s)

1

Abstract

1

Drawing(s)

1

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

18th June 2003



12. Name and daytime telephone number of person to contact in the United Kingdom

David S. Moore
020 7613 0280

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Seal Arrangement

The invention relates to a piston valve unit for a braking system and in particular, but not exclusively, a seal arrangement for a piston valve unit.

In the railway industry, there are standard service intervals and lifetimes for various components. The standard servicing interval for most components is nine years and the component is expected to have a lifetime of forty years. Railway cars also exhibit high usage compared to other land based forms of transport.

Conventional brake systems for railway cars are pneumatically driven and generally use diaphragm valves to control the application and release of pressure to the brake actuators. Considering the normal usage of a railway car, it is expected that the valve will have 44 million open/close cycles between services and a life time of 196 million open/close cycles. Diaphragm valves have been the preferred option historically due to their reliability and robustness, which permits the industry standard servicing intervals and lifetimes to be met.

However, for more modern systems, it is desirable to have electronic control of the brake system to permit new technologies to be introduced. One possibility is the use of a piston valve type arrangement, in which the piston position is toggled between two positions. To maintain the pressure in the valve, the piston is provided with piston rings. However, a significant problem with piston valves is that the wear on the surface of the piston bore and piston ring is high and in many cases leads to failure of the valve between servicing intervals.

The present invention seeks to provide a piston valve unit having a seal arrangement with reduced likelihood of failure between service intervals and a higher operational life for the bore.

According to the invention there is provided a seal arrangement for a sliding seal, which seal arrangement is disposed on a body adapted to move in use, the seal arrangement being adapted to provide a seal between the moving body and a surface of a second body,

wherein the second body is formed of a material having substantially aligned inclusions or micro-cracks formed in the surface of the second body, which inclusions or micro-cracks have a longitudinal direction wherein, in use, the direction of motion of the seal arrangement is substantially parallel to the longitudinal direction of the inclusions or micro-cracks.

In a preferred embodiment, the seal arrangement comprises an O ring, the moving body comprises a piston and the second body comprises a piston bore. Preferably, the seal has a circular cross-section. Preferably, the second body is formed from an extruded material. Preferably, the second body is formed of extruded anodised aluminium. Preferably, the seal is formed of polyurethane.

In a preferred embodiment the seal arrangement is provided in a brake valve arrangement for a railway vehicle braking system comprising a piston valve.

An exemplary embodiment of the invention will now be described in greater detail with reference to the drawings in which:

Fig. 1 shows a piston valve unit.

Fig. 1 shows a piston valve unit for use in a pneumatic railway brake system comprising a main body 1 and a top body 2 disposed on the upper surface of the main body 1, wherein the main body 1 is provided with a piston bore 3, which piston bore is vented by a further bore 5. The main air supply is provided via an air passage 7 having a choke 8 to a first piston bore 3. The air passage 7 then divides with one arm passing to an output stage and the second arm passing to an exhaust passage with a choke 9 at its lower end, which is adapted to vent the valve.

The piston bore 3 have a stepped structure with the narrower cross section located at the lower part of the bore. Each piston bore is provided with a piston 10 having a stepped cross section with the narrower cross section located at the bottom end and the wider cross section located at the upper end. Each section is provided with a piston ring 12. The operation of each valve is controlled by a respective micro-solenoid 13 which controls the

application of a pilot pressure into the respective upper chambers of the valves. The pistons toggle between two positions with a stroke of several millimetres.

The seal 12 is typically a polyurethane O-ring, although other squeeze seal designs are possible, and the body of the valve is made from extruded aluminium. The piston bore 3 is anodised.

The number of sliding operations over which the seals 12 maintain the required performance is dependent on many factors such as material hardness, lubrication, temperature of operation and frictional values of materials.

It has been discovered that the initial surface finish within reasonable tolerances has little effect on the lifetime of the seals 12. However, equally the failure of the sealing arrangement is surprisingly not caused by wear of the ring. The microstructure of the base material surface will typically show many inclusions or micro-cracks. Such inclusions or micro-cracks are generally irregular in shape and so have a longitudinal length which is greater than the lateral width. The hard anodised coating is porous and columns of inclusions extend to the surface undermining the near surface material making this friable, which then in use cause craters. As the seal slides across the craters, approximately perpendicular to the inclusion elongation causing the edges of the crater to crack and eventually break away, thus increasing the size of the crater. The hard particles of aluminium released in this way become trapped between the seal 12 and the piston bore 3 and act as an abrasive both embedding in the seal and wearing away the surface of the piston bore, which in turn will lead to a reduction in sealing efficiency and the failure of the valve.

Surprisingly, it has been further discovered that the inclusions are substantially oriented in the direction that the base material is extruded and that when a sliding force is applied along the inclusion, the surface material exhibits different behaviour and the edges of the crater do not crack to the same extent as with an inclusion having a different orientation. Therefore if the grain structure of the base material forming the piston bores is longitudinally aligned with the direction of motion of the seal, the action of the sliding seal causes the seal to bed in rather than abrade. This provides a greatly increased seal life.

Although the base material has been described as extruded aluminium, it would be possible to use other materials. It would also be possible to use manufacturing techniques other than extrusion as long as these exhibit substantially aligned micro-cracks and inclusions.

Claims

1. A seal arrangement for a sliding seal, which seal arrangement is disposed on a body adapted to move in use, the seal arrangement being adapted to provide a seal between the moving body and a surface of a second body, wherein the second body is formed of a material having substantially aligned inclusions or micro-cracks formed in the surface of the second body, which inclusions or micro-cracks have a longitudinal direction wherein, in use, the direction of motion of the seal arrangement is substantially parallel to the longitudinal direction of the inclusions or micro-cracks.
2. A seal arrangement according to Claim 1, wherein the seal arrangement comprises an O ring, the moving body comprises a piston and the second body comprises a piston bore.
3. A seal arrangement according to Claim 1 or Claim 2, wherein the seal has a circular cross-section
4. A seal arrangement according to any one of Claims 1 to 3, wherein the second body is formed from an extruded material.
5. A seal arrangement according to Claim 4, wherein the second body is formed of extruded anodised aluminium.
6. A seal arrangement according to any one of Claims 1 to 5, wherein the seal is formed of polyurethane.
7. A brake valve arrangement for a railway vehicle braking system comprising a piston valve having a seal arrangement according to any one of Claims 2 to 6.

Abstract

Seal Arrangement

A sliding seal arrangement in particular for a valve having an anodised aluminium coating in contact with the seal. The coating is produced so that inclusions in the surface of the coating are substantially aligned. The direction of motion of the sliding seal in use is then substantially aligned with the direction of the inclusions resulting in greatly reduced wear on the seal.

1/1

